

# UNDER BROILER COUNTER TECHNICAL DATASHEET

## UBC5 UNDER BROILER



UBC5

Dimensions (mm)	External	Internal
Width	1000	587
Depth	782	683
Height	600	399
Drawer opening		1407
<b>Capacity</b>		
Capacity cu.ft/ltrs		5.7/160

## UBC7 UNDER BROILER



UBC7

Dimensions (mm)	External	Internal
Width	1300	589
Depth	782	683
Height	546	345
Drawer opening		1407
<b>Capacity</b>		
Capacity cu.ft/ltrs		6.9/195.5

## UBC20 UNDER BROILER



UBC20

Dimensions (mm)	External	Internal
Width	1962	1470
Depth	782	683
Height	546	345
Drawer opening		1407
<b>Capacity</b>		
Capacity cu.ft/ltrs		12.5/355

## KEY FEATURES

- Space saving solution - designed to accommodate 600mm or 900mm chargrills and griddles depending on model

- Foodsafe stainless steel exterior and interior
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Removable refrigeration system designed for easy service and maintenance
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient

## OPTIONS

- Helicoil cable





# UNDER BROILER COUNTER TECHNICAL DATA

	UBC5	UBC7	UBC20
Temperature (°C)	+1/+4°C	+1/+4°C	+1/+4°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph		
Fuse (Amps)	13	13	13
Defrost	Automatic Off Cycle	Automatic Off Cycle	Automatic Off Cycle
Noise level (dBA)	55	59	59

## Fittings

	UBC5	UBC7	UBC20
Drawers	2	2	4
Containers (100mm deep)	1 x 2/1 GN container	1 x 2/1 GN container	1 x 2/1 GN container
Chargrill/Griddle (not included)	1 600mm unit	2 600mm unit	2 900mm unit

## Electrical / Energy Data - Standard Refrigerant

	UBC5	UBC7	UBC20
Refrigerant	R134a	R134a	R134a
Energy Efficiency Class	C	C	C
Energy Consumption (kW / 24hrs)	2.12	1.98	2.38
Start Up (Amps)	8.7	9.6	9.6
Running (Amps)	1.46	1.89	1.88
Heat Rejection	285	407	407

## Electrical / Energy Data - Hydrocarbon Refrigerant

	UBC5	UBC7	UBC20
Refrigerant	R290	-	R290
Energy Efficiency Class	C	-	C
Energy Consumption (kW / 24hrs)	2.25	-	2.29
Start Up (Amps)	8.7	-	9.5
Running (Amps)	1.8	-	1.86
Heat Rejection	476	-	484

## IMPORTANT NOTES:

\*Energy consumption is tested to EN16825 in 24hrs

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

